

CHAPTER 11

SCSI

This chapter presents the requirements and recommendations for the small computer system interface (SCSI).

SCSI is a flexible I/O bus that is used in the design of a wide variety of peripherals, including disk drives, CD drives, tape drives, scanners, and magneto-optical drives. The SCSI host adapter is the circuitry that serves as an interface between the system and one or more SCSI peripherals. A host adapter can be a card that plugs into the system's expansion bus, such as a PCI card, or it can be designed directly into the system board.

The use of SCSI in a PC 99 system is optional, but if SCSI is used, all components must comply with the requirements defined in this chapter.

Contents

SCSI Host Adapter Requirements	152
SCSI Peripheral Requirements	154
Plug and Play for SCSI Host Adapters and Peripherals.....	154
Power Management for SCSI Devices.....	156
SCSI References	157
Checklist for SCSI.....	157

SCSI Host Adapter Requirements

This section summarizes class specifications and standards for SCSI host adapters.

11.1. SCSI host controller supports bus mastering

Required

The host controller must support PCI bus mastering; PCI bus mastering must be enabled by default.

11.2. Bootable SCSI controller supports El Torito No Emulation mode

Required

A bootable SCSI storage controller must support the No Emulation mode defined in *El Torito—Bootable CD-ROM Format Specification, Version 1.0*, or an equivalent method that supports the Windows NT CD-ROM installation process.

11.3. Option ROM supports Int 13h Extensions

Required

The Int 13h Extensions ensure correct support for high-capacity drives, consistent drive-letter mapping between real and protected modes, and other capabilities for both Windows and Windows NT. Support for the fixed-disk access subset of Int 13h Extensions must be provided in the system BIOS and in any option ROMs for storage devices that include BIOS support.

The Int 13h Extensions are defined in the “Layered Block Device Drivers” section of the Windows 95 DDK and in the Windows NT 5.0 DDK.

11.4. Option ROM supports virtual DMA services

Required

Plug and Play SCSI host adapters must support virtual DMA services in the host-adapter option ROM and must support bus mastering. Virtual DMA supports scatter/gather capabilities, solving the problem of mapping linear addresses (segment:offset) into physical addresses.

11.5. Bus type is clearly indicated on connectors for all adapters, peripherals, cables, and terminators

Required

Connectors for each SCSI adapter, peripheral, cable, and terminator must be clearly labeled to indicate the bus type. All external SCSI connectors must display the appropriate SCSI icon defined in *Small Computer Interface Parallel Interface (SPI) standard, Annex H*, and must display any clarifying abbreviations or acronyms. The following are applicable acronyms and their definitions:

- **DIFF** – differential. A signaling method that employs differential drivers and receivers to improve signal-to-noise ratios and increase maximum cable lengths. This includes both low voltage differential (LVD) and high voltage differential (HVD) types.
- **SE** – single-ended. A signaling method that employs drivers and receivers to increase circuit density.
- **LVD** – low voltage differential. A signaling method similar to DIFF but with lower signaling voltages supporting higher transfer rates.

11.6. Differential devices support DIFFSENS as defined in SPI standard*Required*

Without DIFFSENS, the differential bus drivers, a single-ended device, or both could be damaged if a single-ended device is connected to a differential bus.

The standard for DIFFSENS is defined in Section 5.4.2 of the SPI standard.

11.7. Automatic termination circuit and SCSI terminators meet SCSI-3 standard*Required*

SCSI add-on adapters and on-board controllers must use automatic termination, which allows a user to add external devices without removing the PC case. Terminators used in the SCSI host adapter must be regulated terminators, also known as active, SCSI-3 SPI, SCSI-2 alternative-2, or Boulay terminators. SCSI termination built onto internal cables must meet SCSI-3 standard.

11.8. Terminator power is supplied to the SCSI bus with over-current protection*Required*

This requirement has two components:

- **11.8.1 Host adapter must supply terminator power.** The base requirement for system-board implementations using PCI or another expansion bus is that the host adapter must supply terminator power (TERMPWR) to the SCSI bus. All terminators on the host adapter, as well as those on the internal and external SCSI bus, must be powered from the TERMPWR lines on the SCSI bus.
- **11.8.2 The circuit that supplies TERMPWR must have built-in overcurrent protection.** Devices that provide TERMPWR must also provide some means of limiting the current through use of a self-resetting device. For example, a positive-temperature coefficient device or circuit breaker can be designed into the circuit. These devices open during an over-current condition and close after the condition ends.

Mobile PC Note

Although recommended, this item is not required for battery-powered systems that implement the SCSI host adapter as a PC Card device, because of battery consumption issues.

11.9. External connector meets SCSI-2 or later standard*Required*

Although an external connector is optional, if an external connector is provided, it must be a high-density connector and must meet the requirements defined in the SCSI-2 or later standard.

11.10. Controller and peripherals implement SCSI bus parity signal*Required*

The SCSI host adapter and all SCSI peripherals must implement the SCSI bus data protection signal defined in the SPI standard, and data protection must be enabled by default.

SCSI Peripheral Requirements

This section summarizes requirements related to specifications and standards for SCSI peripherals.

11.11. SCSI connections use keyed and shrouded connectors

Required

For internal and external configurations, the SCSI bus cable must be plugged into shrouded and keyed connectors on the host adapter and devices. This ensures that the cable is properly positioned so the user cannot plug in cables incorrectly.

For internal configurations, pin 1 orientation must be designated on one edge of the ribbon cable and also on the keyed connector of the SCSI peripheral device. For more information, see requirement 3.18, “Connections use icons, plus keyed or shrouded connectors, with color coding.”

11.12. External devices use automatic termination or an accessible on-board termination switch

Required

The recommended implementation for an external SCSI peripheral device is to provide automatic termination. In the absence of automatic termination, a mechanical means must be provided for setting termination and the switch must be accessible to the user without opening the device chassis.

11.13. Shielded device connector meets SCSI-2 or later standard

Required

Device connectors must meet the standards defined in the SCSI-2 or later standard.

11.14. Removable media devices support media status notification

Required

SCSI removable media storage devices must support media status notification as specified in requirement 18.2, “Removable media devices support media status notification.”

CHANGED FOR
V.0.9

Plug and Play for SCSI Host Adapters and Peripherals

This section summarizes the Plug and Play requirements for SCSI devices.

11.15. Each device has a Plug and Play device ID

Required

For each system-board device, there must be a Plug and Play device-specific ID.

Each SCSI controller or peripheral device must provide device IDs as defined in the *Plug and Play SCSI Specification, Version 1.0*, and in the specification for the bus it uses as defined in the related chapter in Part 3 of this guide.

For example, a PCI device must comply with PCI 2.1 and also must provide a Subsystem ID and Subsystem Vendor ID as defined in Chapter 9, “PCI.” PCI controllers integrated into core logic on the system board do not have to provide Subsystem IDs and Subsystem Vendor IDs, but must meet other PCI 2.1 requirements.

11.16. Dynamic resource configuration is supported for all devices*Required*

For SCSI on-board controllers and add-on adapters, the system must be capable of automatically assigning, disabling, and relocating the resources used by the device. Configuring the device or adding it to the system must not require changing jumpers or switches on either the device or the system board.

In the event of an irreconcilable conflict with other devices, the operating system must be able to disable the adapter. Disabling a device must result in freeing its resources for use by other devices.

Note: This requirement does not apply to jumper settings used by the OEM to make basic system-related settings in the factory. This requirement applies only to settings that the end user must make to configure the hardware.

11.17. Resource configuration meets bus requirements*Required*

Plug and Play resource-configuration requirements are defined by the bus used by the SCSI controllers and peripheral devices, as defined in the related chapter for the specific bus in Part 3 of this guide.

11.18. SCAM support is disabled by default*Required*

SCSI Configured Automatically (SCAM) support is not recommended. If support is present, it must be disabled by default. SCAM is not supported by Windows operating systems; enabling SCAM can cause the system to become unstable or inoperable.

Plug and Play for SCSI must be implemented as defined in *Plug and Play SCSI Specification, Version 1.0*.

NEW FOR V.0.9

11.19. SCSI devices that support hot-plugging meet PC 99 requirements*Required*

To ensure reliable support for hot-plugging capabilities, the following requirements must be met by any SCSI devices that allow hot-plugging:

- **11.19.1 Hot-plugging for PCI devices uses ACPI-based methods.** Windows 98 and Windows NT 5.0 support dynamic enumeration, installation, and removal of devices connected by way of the PCI bus only if there is a supported hardware insert/remove notification mechanism as defined in Section 5.6.3 of the ACPI 1.0 specification.

In order to properly function with the native support in the operating system, developing industry standards such as those referred to as PCI Hot Plug and Compact PCI must use ACPI-based methods for supporting hardware insertion and removal as defined in the ACPI 1.0 specification.
- **11.19.2 All removable media support media status notification.** Removable media must support the appropriate media status notification method to ensure that no loss of data or system failure results when such media is removed from the system. See requirement 11.14, “Removable media devices support media status notification.”

Recommended: A locking mechanism to ensure that devices are removed only under operating system control or during sleep or off states. For implementation details and additional design guidelines, see the article about hot-plugging support at http://www.microsoft.com/hwdev/busbios/rem_devs.htm.

11.20. SCSI controllers provide multi-initiator support*Recommended*

Multi-initiator support allows two SCSI controllers—each installed in a separate computer system—to coexist on a shared SCSI bus with a set of shared devices. If this capability is supported, the SCSI IDs must be changeable from the default SCSI controller ID of 7 and the boot-time SCSI bus reset operation must be able to be disabled on each controller attached to a shared bus.

This capability is recommended for hardware that will be used on systems using the clustering service available under Microsoft Windows NT Server Enterprise Edition. To use this service, a SCSI adapter and a SCSI peripheral must provide multi-initiator support for at least two initiators.

Power Management for SCSI Devices

This section summarizes the specific power management requirements for the SCSI bus class. Power management requirements for other device classes are defined in Part 4 of this guide.

11.21. Bus and device meet PC 99 power management requirements*Required*

Storage devices must comply with the *Storage Device Class Power Management Reference Specification, Version 1.0* or later. The ability to cause a wake-up event as defined in *Storage Device Class Power Management Reference Specification* is an optional feature.

Additional power management requirements are specified based on industry-defined standards for the bus used by the controller, as defined in the related chapter for the specific bus in Part 3 of this guide. See also Part 4 of this guide for the related device class power management requirements for a particular device type.

CHANGED FOR
V.0.9

For mobile drives, it is recommended that a Read operation typically be completed within 5 seconds of applying power or issuing a START UNIT command; for desktop systems, the recommendation is 10 seconds.

The drive spinup time recommendation is not expected to become a requirement in future versions of this guide.

11.22. Hardware supports the STOP/START UNIT command as defined in the SPI standard*Required*

SCSI peripherals must be able to fully recover from a software-initiated spin down without rebooting the system or cycling power. To properly support power management on SCSI drives and to ensure that the operating system responds to appropriate driver calls, the STOP/START UNIT command must be implemented as defined in the SPI (SCSI-3) standard.

11.23. STOP/START UNIT command is used to decrease power consumption*Required*

Wherever appropriate, such as for storage disks, the STOP UNIT command must be used to decrease the power consumption of the base platform.

Removing power should not be used as the method for spinning down storage disks.

SCSI References

The following represents some of the references, services, and tools available to help build hardware that is optimized to work with Windows operating systems.

Compaq, Intel, Phoenix BIOS Boot Specification, Version 1.01

El Torito—Bootable CD-ROM Format Specification, Version 1.0

<http://www.ptltd.com/techs/specs.html>

MMC-2 Multi-Media Command Set-2 Revision 6a

<ftp://ftp.symbios.com/pub/standards/io/t10/drafts/mmc2/mmc2r6a.pdf>

Microsoft Windows 95 DDK and Windows NT DDK

MSDN Professional membership

NCITS Reduced Block Commands (RBC) Draft Proposal (T10/97-260r0)

<ftp://ftp.symbios.com/pub/standards/io/t10/drafts/rbc/>

PCI Local Bus Specification, Revision 2.1 (PCI 2.1)

<http://www.pcisig.com>

Plug and Play SCSI Specification, Version 1.0

<http://www.microsoft.com/hwdev/respec/>

Small Computer Interface (SCSI-2) [X3T9.2-375R] standard

Small Computer Interface (SCSI-3) Parallel Interface (SPI)

[X3T9.2/91-10] standard

Other SCSI standards and documents

Global Engineering Documents

Fax: (303) 397-2740

Phone: (800) 854-7179 (U.S.)

(613) 237-4250 (Canada)

(303) 792-2181 (Outside North America)

SCSI draft standards and other working documents are available at

<ftp://ftp.symbios.com/pub/standards/io/t10/>

Small Form Factor (SFF) Committee publications

FaxAccess: (408) 741-1600 (fax-back)

Fax: (408) 867-2115

Storage Device Class Power Management Reference Specification, Version 1.0

Other device class power management reference specifications

<http://www.microsoft.com/hwdev/onnow.htm>

Checklist for SCSI

If a recommended feature is implemented, it must meet the requirements for that feature as defined in this document.

11.1. SCSI host controller supports bus mastering

Required

11.2. Bootable SCSI controller supports El Torito No Emulation mode

Required

11.3. Option ROM supports Int 13h Extensions

Required

11.4. Option ROM supports virtual DMA services

Required

- 11.5. Bus type is clearly indicated on connectors for all adapters, peripherals, cables, and terminators
Required
- 11.6. Differential devices support DIFFSENS as defined in SPI standard
Required
- 11.7. Automatic termination circuit and SCSI terminators meet SCSI-3 standard
Required
- 11.8. Terminator power is supplied to the SCSI bus with over-current protection
Required
- 11.9. External connector meets SCSI-2 or later standard
Required
- 11.10. Controller and peripherals implement SCSI bus parity signal
Required
- 11.11. SCSI connections use keyed and shrouded connectors
Required
- 11.12. External devices use automatic termination or an accessible on-board termination switch
Required
- 11.13. Shielded device connector meets SCSI-2 or later standard
Required
- 11.14. Removable media devices support media status notification
Required
- 11.15. Each device has a Plug and Play device ID
Required
- 11.16. Dynamic resource configuration is supported for all devices
Required
- 11.17. Resource configuration meets bus requirements
Required
- 11.18. SCAM support is disabled by default
Required
- 11.19. SCSI devices that support hot-plugging meet PC 99 requirements
Required
- 11.20. SCSI controllers provide multi-initiator support
Recommended
- 11.21. Bus and device meet PC 99 power management requirements
Required
- 11.22. Hardware supports the STOP/START UNIT command as defined in the SPI standard
Required
- 11.23. STOP/START UNIT command is used to decrease power consumption
Required